



Hikvision High-End Surveillance Guide

- Products generally used and specified in larger projects & tenders
- Order on demand products (not kept in stock)



VIDEO SURVEILLANCE



INTRUSION DETECTION



FIRE DETECTION



PUBLIC ADDRESS / EVAC SYSTEMS



ACCESS CONTROL



MANAGEMENT SYSTEMS

International distributors of Artec, Bosch, Hikvision, IDEMIA, Impro, Ligowave & Virdi products

Gauteng • Western Cape • Eastern Cape • KwaZulu-Natal

Other product guides available on request:

- Hikvision Run Rate Product Guide
- Hikvision Access Control & Intercom Systems
- Access Control & Biometric Solutions (Impro, Morpho & Virdi)
- Bosch Fire Alarm Systems
- Bosch Public Address/EVAC Systems
- LigoWave Wireless Solutions



Network Cameras



DS-2CD4A26FWD-IZS/P
Automatic Number-plate Recognition
"Darkfighter" Smart ANPR Network Camera

- ANPR Software Loaded
- Motorized 2.8~12 or 8~32mm lens
- Up to 50m IR range & 100m for the longer lens



DS-2CD7A26G0/P-IZS
Automatic Number-plate Recognition
DeepinView Outdoor VF Bullet Network Camera

- High accuracy face detection
- Perimeter protection, based on deep learning powered target detection - line crossing, intrusion, region entrance / exit



DS-2CD6365G0-IVS
360° Panoramic View
Hikvision 6-MP 360° Infrared Fisheye Network Camera

- Heat map with deep learning algorithm
- 6 behaviour analyses
- Up to 15 live view display modes



DS-2CD6425G0-20
Covert Operations
2-MP Block-shaped Lens Network Covert Camera

- 120dB WDR; 3D DNR
- 4 behaviour analyses
- 0.005 Lux low light performance



DS-2DE4225IW-DE
Wide Area Coverage
Outdoor 25X 2-MP IR Network PTZ Camera

- Regional Exposure & Focus
- Up to 100 m IR distance
- WDR, BLC, 3D DNR, Defog, EIS



DS-2DF8225IX-AEL(B)
Darkfighter Power
Outdoor 2-MP 25X Ultra-low Light Network PTZ Camera

- Deep-learning technology
- Perimeter Protection Features
- IR distance: 200m
- 24 VAC & Hi-PoE; IP67



DS-2PT3326IZ-DE3
360° Images with Multiple Cameras
PanoVu Outdoor Mini Series IR Network PTZ Camera

- Smart detection: Motion -; Video tampering - & Exception
- 3-ch panoramic images
- 1-Ch 2-MP PTZ



DS-2CD6924F-IS
Four x 2-MP Cameras
Outdoor 8-MP PanoVu Panoramic Dome Camera

- Darkfighter technology
- 4 x IR LEDs, up to 20 m IR
- 6 behaviour analyses
- Full 180° view



Network Cameras *(continued)*



DS-2CD6D54FWD-IZS
Line Crossing-, Intrusion- & Region Entrance Detection Outdoor EXIR Flexible PanoVu Network Camera

- 4 flexible camera modules
- 2.8-12mm motorised lenses
- 6 behaviour analyses
- IP67, IK10 vandal proof



DS-2DP0818ZIX-D/236
"No place to hide" Camera Outdoor PanoVu Series 180° Panoramic + 36X PTZ Camera

- **Panoramic Camera:** 4 x sensors, forming a 180° stitched image
- **Tracking PTZ Camera:** Pan & tilt range: 360°; IR: 200 m



DS-2TD2136-15
Single Lens Thermal Camera Thermal Network Bullet Camera with 15mm Lens

- Advanced Fire Detection
- Support mirror image
- Audio & Alarm I/O
- PoE, 24vAC, 12vdc



DS-2TD2836-50
Dual Lens Thermal Camera Thermal & Optical Network Bullet Camera

- **Thermal Module:** Max res: 384 x 288; Lens: 50mm.
- **Optical Module:** 1920 x 1080; Lens: 25mm; WDR; IR: 100 m



DS-2TD4136-25/50
Perimeter Defence & Fire-prevention Purposes Thermal & Optical Bi-spectrum Network Speed Dome

- Advanced fire detection
- Thermal module: Lens: 25/50 mm
- Optical camera: x36 PTZ; IR: 200 m; WDR



DS-2CD7126G0/L-IZS
Artificial Intelligence: Queue Management 2-MP WDR IR 30 m VF Dome Network Camera

- Count people in the queue
- Queue data reports
- 2.8 to 12 mm motor-driven lens



iDS-2CD8426G0/F-I
Artificial Intelligence: Face Recognition DeepinView Dual-Lens WDR Face Recognition Camera

- Advanced deep learning algorithm & instant face detection, capture and comparison



iDS-2CD6810F/C
Artificial Intelligence: People Counting Dual Lens Intelligent People Counting Network Camera

- Specialized people counting function
- People entering, exiting, passing by
- Dual lens and dual CPU



DS-K1T606MF
AC & Intercom: Face Recognition 2-MP Dual-lens Face Recognition Terminal

- 3000 face pictures & 5 000 fingerprints storage
- Accurate and fast face recognition function

Artificial Intelligence – The Present and Future for Video Surveillance

HIKVISION'S latest high end cameras harnesses the power of Hikvision's Deep Learning AI solution, and in conjunction with Hikvision's Deep in Mind network video recorder, offers facial capture, human body detection, ANPR, heat mapping and queue management in real-time.

It incorporates Darkfighter technology with WDR capabilities of 140dB! In this range we find specialized cameras for behavioural analysis, Face Recognition, People Counting, 360 Target Capture and tracking with full body, dome, anti-corrosion and bullet form factors.

Hikvision is leading the market in AI and these cameras are the next step in providing actionable video content and analysis for all market verticals.



Network Keyboards



DS-1005KI
Uncomplicated to Operate Hikvision USB Keyboard

- Joystick: 3-axis control, rotating zoom
- Up to 15 programmable buttons
- USB connection



DS-1006KI
The Latest RS-485 Keyboard with 128 x 64 LCD Screen

- 4-axis joystick
- Control DVR, NVR and PTZ dome
- Connectable to the Multi-functional Video Centre



DS-1100KI
View Video on Keyboard 7" TFT LCD Touch Panel Network Keyboard

- PTZ dome, video decoder & DVR control
- Support 15 users
- USB 2.0 interface for video backup



Network Recorders



DS-7616NI-K2
Professional and Reliable
16-Channel Embedded NVR

- Up to 8-MP resolution recording
- HDMI output up to 4K resolution
- HDD: 2 SATA interfaces (< 8 TB)



DS-7716NI-I4/16P(B)
"Plug & Play"
16-Channel NVR with PoE

- 16 Independent PoE network interfaces
- HDD: 4 SATA interfaces (≤ 8 TB)
- Dual HDMI output



DS-7732NI-I4(B)
Dual-OS Design to Ensure High Reliability
32-Channel High End NVR

- Up to 12-MP resolution recording
- HDD: 4 SATA interfaces (≤ 8 TB)
- Dual HDMI



DS-7732NI-I4-16P(B)
300m Extended PoE Support
32-Channel High End NVR with PoE

- 16 Independent PoE network interfaces
- Dual HDMI & VGA output
- HDD: 4 SATA interfaces (≤ 8 TB)



DS-9632NI-I8
Support POS Function
32-Channel Professional NVR

- Up to 32-ch 12 MP IP cameras can be connected
- HDD: 8 SATA interfaces (≤ 10 TB)
- RAID types supported



DS-9664NI-I8
HDD Hot Swap
64-Channel Professional NVR

- HDMI1 output at 4K & VGA1 output @2k resolution
- In-/Out bandwidth: 320/256
- Hard disk: 8 SATA interfaces (≤ 10 TB)



iDS-9632NXI-I8/16S
Artificial Intelligence: Behaviour Detection
32-Channel Intelligent "DeepinMind" NVR

- Dual-recognition of up to 16-Ch human body recognition
- HDD: 8 SATA interfaces (≤ 8 TB)
- Alarm in/out: 16/4; 2x Audio output



iDS-9632NXI-I8/4F
Artificial Intelligence: Face Detection & Analysis
Hikvision DeepinMind NVR

- More precise face recognition and analytics
- Powerful face pictures library management
- HDD hot swapping with RAID 0/1/5/6/10



Hikvision Software

HikCentral Central Management System

The newly released HikCentral is a comprehensive, AI-empowered surveillance platform that makes easy and convenient central management available everywhere it is needed. In order to provide project-specific solutions, additional functions and services from collaborative partners are essential. Therefore, the video management platform is designed to be Central, Collaborative, and Intelligent.

The Advanced Functionality Of HikCentral

HikCentral contains the following advanced functions: Advanced Live View • Advanced Playback • Thermal Imaging Queue Detection • Smart Wall • pStor (Windows Based NVR) • Video linkage with Access Control • Enhanced Alarm Management • Professional UVSS • 3rd-party Integration under OpenSDK

Software Packages

Base License Software
Site License Software
Video Surveillance Base License Software
Channel License Software
Access Control Base License Software
Door Access Channel License Software
Video Wall Base License Software
ANPR Base License Software
Facial Recognition Base License Software
UVSS Base License Software
Time & Attendance Base License Software





Display Equipment



DS-D5019QE-B LED Backlit Technology Hikvision 18.5" LED Monitor

- 3D comb filter
- 3D De-interlace
- 3D noise reduction
- Input: HDMI, VGA
- VESA stand bracket (included)



DS-D2046NL-B Samsung DID Ultra-slim Panel Technology Hikvision 46" LCD Display Unit

- Multiple loop output interfaces support self-joint of multiple signals
- Dimensions: 1023.8x579x132 mm
- Optional: Modular monitor brackets (Pedestal - & frame part)



DS-D2049NL-B Samsung DID Ultra-slim Panel Technology Hikvision 49" LCD Display Unit

- Multiple loop output interfaces support self-joint of multiple signals
- Dimensions: 1077.6x607.8x113.57 mm (WxHxD)
- Optional: Modular monitor brackets (Pedestal - & frame part)



DS-D2055NL-B/G Samsung DID Ultra-slim Panel Technology Hikvision 55" LCD Display Unit

- Multiple loop output interfaces support self-joint of multiple signals
- Dimensions: 1213.5x684.3x112.9 mm (WxHxD)
- Optional: Modular monitor brackets (Pedestal - & frame part)



Decoders



DS-6904UDI DS-6900 Series 4-Ch HDMI Output Decoder (4K&H.265)

- Provides HDMI, VGA, and BNC output interfaces
- Audio/Video decoding: Up to 12-MP, 32 decoding channels
- Input: VGA/DVI/RJ45



DS-6908UDI DS-6900 Series 8-Ch HDMI Output Decoder (4K&H.265)

- BNC output: 4-ch, 2 DB 15; Input: VGA/DVI/RJ45
- Audio/Video decoding: Up to 12MP, 64 decoding channels



DS-6916UDI DS-6900 Series 16-Ch HDMI Output Decoder (4K&H.265)

- Provide HDMI (adaptable to DVI-D) & BNC output interfaces
- BNC output: 8-Ch, 2 DB 15; Input: VGA/DVI/RJ45
- Audio/Video decoding: Up to 12MP, 128 decoding channels



Infrastructure: Switches



DS-3E0105P-E Plug-and-Play Installation 4-Port 100 Mbps Unmanaged Economical PoE Switch

- 4 x 10/100 Mbps Auto-MDIX ports
- Extended mode for long cable runs
- 4 kV surge protection



DS-3E1318P-E Plug-and-Play Installation 16-Port 100 Mbps Web- managed PoE Switch

- 8-core power supply technology
- 250 m extended PoE support
- 4 kV surge protection



DS-3E1326P-E Plug-and-Play Installation 24-Port 100 Mbps Web- managed PoE Switch

- 8-core power supply technology
- 250 m extended PoE support
- 4 kV surge protection



DS-3E2326P High end performance 24-Port 100 Mbps Base-T PoE Switch

- Supports the telecom-level Ethernet-ring protection protocol
- Layer 2 full managed
- Surge protection

Should you require a Hikvision product which does not appear on this pricelist, you are welcome to contact your sales consultant or nearest Sensor branch and request, either a quotation or comprehensive pricelist.

Sensor Gauteng
Midrand, Gauteng
South Africa
Tel: +27 (0)11 314 9419

Sensor Eastern Cape
Port Elizabeth, Eastern Cape
South Africa
Tel: +27 (0)41 581 0316

Sensor Western Cape
Cape Town, Western Cape
South Africa
Tel: +27 (0)21 914 7557

Sensor Kwa-Zulu Natal
Durban, Kwa-Zulu Natal
South Africa
Tel: +27 (0)31 263 0305/6/7

Website: www.sensorsecurity.co.za